

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (currently amended) A pipe coupling for joining a first pipe to pipes of varying diameters, comprising,
a first hollow fitting having opposite first and second ends,
with the first end being adapted for connection to a first pipe and having a sleeve with ~~a typically~~ an inwardly crimped detent,
a second hollow fitting having first and second ends with the second end having a groove for receiving the detent of the first hollow fitting to define a fluid conduit extending through interiors of the first and second hollow fittings, first and second adjacent wells in the second hollow fitting, with the first well being adjacent the second end of the second fitting and having an upper end terminating in the first well, with both the first and second wells comprising at least a part of the fluid conduit,
the first and second wells being cylindrical in shape with the second well having a diameter greater than the diameter of the first well, whereupon inlet pipes having outside diameters complimentary in size to the diameters of the wells can be selectively and alternately secured within the respective wells to fluidly connect such pipes to the fluid conduit and the first hollow fitting.

2. (previously presented) The pipe coupling of claim 1 wherein the first and second wells have side walls adaptable for being fixedly secured to the inlet pipes.

3. (previously presented) The pipe coupling of claim 1 wherein the first hollow fitting is comprised of metal and the second hollow fitting is comprised of plastic.

4. (cancelled).

5. (previously presented) A pipe coupling for joining a first pipe to pipes of varying diameters, comprising,
a first hollow fitting having opposite first and second ends,
with the first end being adapted for connection to a first pipe,
a second hollow fitting having first and second ends with the
second end fitting slidably within the second end of the
first hollow fitting in sealed condition to define a fluid
conduit extending through interiors of the first and second
hollow fittings,
first and second adjacent wells in the second hollow fitting,
with the first well being adjacent the second end of the
second fitting and having an upper end terminating in the
first well, with both the first and second wells comprising
at least a part of the fluid conduit,
the first and second wells being cylindrical in shape with the
second well having a diameter greater than the diameter of
the first well, whereupon inlet pipes having outside
diameters complimentary in size to the diameters of the
wells can be selectively and alternately secured within the

respective wells to fluidly connect such pipes to the fluid conduit and the first hollow fitting; and wherein one of the wells is adapted to secure a pressurized fluid supply pipe therein.

6. (previously presented) The coupling of claim 1 wherein the first hollow fitting has means on its first end for coupling to a first pipe.

7. (currently amended) The coupling of claim 5 wherein a at least one well is adapted to adhesively secure has adhesive therein for securing the well to a pressurized fluid supply therein.